



- Class I or II flamespread.
- Panel widths can vary up to 5'-0" for 10mm and 16mm and 4'-0" for 25mm.
- Panel lengths up to 40'-0" for 10mm, 16mm or 25mm and up to 20'-0" long for Venetian and panels requiring Nanogel® filling.
- Panels can be curved (cold formed) to a radius as small as 5'-9" for 10mm, 9'-2" for 16mm and 14'-4" for 25mm. (175 times the thickness of the panel).
- Panels can be fabricated to any shape not limited to rectangular shapes.
- Up to 5'-0" unsupported spanning capabilities – depending upon design load, panel width and thickness.
- Allows for unrestricted linear/lateral panel movement.
- Can sustain high winds and gravity.
- Impact resistance of 200 ft. lbs.
- Unsupported spanning capabilities up to 17'-0" with EDGE MAX®.
- Ten (10) year guarantee.
- Standard Colors: Clear, Opal, Bronze.
- Premium Colors: White, Green, Venetian.

EDGE® & EDGE MAX® Unique Features

- **U-Value**
EDGE®: 10mm = 0.52; 16mm = 0.42; 25mm = 0.28
EDGE MAX®: (10mm/10mm) = 0.26
- **Light Transmission**
EDGE® = 20% to 80%
EDGE MAX® = 4% to 66%
- **Shading Coefficient**
EDGE® = 0.45 to 0.98
EDGE MAX® = 0.28 to 0.94



Winnie Palmer Hospital for Women & Babies
Orlando, Florida
Architect: Jonathon Bailey Associates
System: EDGE®